

STA-LUBE Synthetic Brake & Caliper Grease is the highest quality synthetic brake and caliper grease available. Formulated from proprietary bases, extreme pressure additives, molybdenum disulfide (MOLY), graphite and PTFE. **STA-LUBE Synthetic Brake & Caliper Grease** will not damage rubber or plastic components, freeze, melt or wash-out. Properly lubricating your brake system will ensure optimum braking efficiency, even pad wear and extended brake life.

APPLICATIONS:

All Disc, Drum and ABS brake systems

Disc Brakes

- Shimmed disc brake pads
- Rotor hats (Underside)
- Caliper slides, bolts & pins
- All metal-to-metal contact points

Drum Brakes

- Shoe landings (Bosses)
- Brake hardware
- Parking brake hardware & cables
- Drum brake adjusters



**SYNTHETIC
BRAKE &
CALIPER GREASE**

GRASA SINTÉTICA PARA FRENOS Y MORDAZAS

Part No. SL3303

Net Wt. 12 OZ. (340 g)

**USE ON EVERY
BRAKE JOB!**

**CONTAINS
MOLY, PTFE &
GRAPHITE**

**TEMPERATURE
RANGE
-30°F TO 600°F***

**PREVENTS
BRAKE NOISE**

**MAXIMIZES
BRAKE
EFFICIENCY**

DIRECTIONS: Read entire label before using this product. Use on every brake job. Thoroughly clean all brake parts with CRC Brakleen®, remove all rust and corrosion using sandpaper or a wire brush. Lubricate all metal-to-metal contact points with a light coating of **STA-LUBE Synthetic Brake & Caliper Grease**.

Do not use on internal caliper pistons or wheel stud/nut threads.

WARNING: Contains petroleum oils 72623-87-1, polyisobutylene 9003-27-4, silica 7631-86-9, molybdenum disulphide 1317-33-5 and natural graphite 7782-42-5. For additional information, consult SDS for this product.

DISPOSAL: All used and unused product should be disposed of in conformance with applicable regulations.

KEEP AWAY FROM CHILDREN

*600°F is intermittent working temperature

Sta-Lube® is a wholly-owned subsidiary of CRC Industries, Inc.
©2014 CRC Industries, Warminster, PA 18974
Technical Service: 800-521-3168
Customer Service: 800-272-8963
SDS: 215-442-6260
www.crcindustries.com

