



# Pipe Thread Sealant

**Thread Sealing Compound with PTFE**

**Non-Hardening • Non-Toxic  
Prevents Corrosion**

KEEP AWAY FROM CHILDREN.  
Read warnings on back panel.

**Net Weight 8 oz. (227 g)**

*Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite [www.crcindustries.com](http://www.crcindustries.com).*



**No. SL35401**



## CRC Pipe Thread Sealant

**CRC Thread Sealant** is a non-toxic, non-drying thread sealing compound consisting of a blend of non-melting grease, PTFE particles and other inert solid fillers engineered to produce a leak-proof seal. Does not contain lead, graphite, molybdenum disulfide, or clay fillers.

**CRC Thread Sealant** can be used to seal all threaded joints in plastic, aluminum, monel, or stainless steel lines against water, natural gas, LPG, gasoline and other services. It is also effective on connections, pipe bungs, bolts, flange seals, and as a gasket-parting compound.

- Contains PTFE
- Prevents Corrosion
- Non-Hardening
- Positive Seal
- Non-Toxic
- Holds Pressure to 8,000 PSI

**DIRECTIONS:** *Read entire label before using this product.* For best results, clean threads of oil, dirt and grease. Apply liberally on male threads only. Joint may be made up immediately or later as desired.

**Precautionary Statements:** Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Observe good industrial hygiene practices. Store away from incompatible materials. Dispose of waste and residues in accordance with local authority requirements.

**First Aid:** Wash hands after handling.

Contains Titanium dioxide (13463-67-7) and Zinc oxide (1314-13-2). For additional information, consult SDS for this product.

©2014 CRC Industries, Inc., Warminster, PA 18974  
Made in U.S.A. 14A  
[www.crcindustries.com](http://www.crcindustries.com)

800-521-3168 (Technical Information)  
800-272-4620 (Customer Service)  
215-442-6260 (SDS)