



COPPER

ANTI-SEIZE

& LUBRICATING COMPOUND

- GENERAL PURPOSE LUBRICANT
- PROTECTS TO 1800°F (982°C)
- MEETS MIL-PRF-907E

Net Wt. 8 oz. (227 g) Part No. SL35901

Read warnings on back panel.



CRC® Copper Anti-Seize is a general purpose anti-seize lubricant that prevents seizing caused by high temperatures, heavy loads, vibrations and corrosion. This unique formulation has been designed with a smooth texture and fine particle size to make it highly suitable for closely fitting parts.

- Protects from -65°F (-54°C) to 1800°F (982°C).
- Prevents seizing and galling of threaded surfaces.
- Saves time by joining mating surfaces faster and easier.
- Reduces costly downtime and breakage.
- Prevents rust and corrosion.
- Torque coefficient (k) 0.10 on steel nuts and bolts.

CRC® Copper Anti-Seize is recommended for use on bolts, bushings, fittings, flanges, gaskets, headers, manifolds, nuts, packings, pipes, plugs, screws, studs, threaded surfaces and wire rope.

Sta-Lube®
©1998 CRC Industries Inc.
Warminster, PA 18974
Tech. Info. 800-521-3168
Cust. Serv. 800-272-4620
Made in U.S.A. 98B

Directions: Please read entire label before using this product.

1. Clean scale and old compound from thread surfaces. **NOTE:** *When grinding or wire brushing, use a dust mask.*
2. Coat mating surfaces and assemble.
3. To avoid contamination, keep container closed when not in use.
4. Not for use on oxygen systems.

WARNING: Contains Petroleum Distillate 64742-52-5, AL Complex Soap 82980-54-9, Petroleum Distillate 64742-57-0, Copper 7440-50-8, Graphite 7782-42-5. Frequent or prolonged contact may cause irritation. Avoid contact with skin and eyes. Do not take internally. **FIRST AID:** In case of contact, flush affected area thoroughly with soap and water. If swallowed, **do not induce vomiting.** Seek medical attention for overexposure. For Industrial Use Only.

KEEP AWAY FROM CHILDREN

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

