



Nickel Anti-Seize and Lubricating Compound

Resists Acid, Chemical Corrosion
& Oxidation

Protects To 2400°F (1316°C)

Meets MIL-PRF-907E

Read warnings on back panel.

No. SL35913

Net Wt: 1 lb (454 g)

*Para obtener las
instrucciones completas
de uso y advertencias de
seguridad del producto
en Español, visite
www.crcindustries.com.*



CRC® Nickel Anti-Seize is a nickel-based formula that is free of copper, lead, sulfides and chlorides. This premium quality lubricant has extremely high temperature and chemical resistance.

- Protects from -65°F (-54°C) to 2400°F (1316°C).
- Prevents seizing of threaded surfaces.
- Chemically inert nickel formulation is safe for use with most chemicals that are unstable with copper.
- Will not poison catalyst beds, reaction chambers or special alloy fittings.
- Torque coefficient (k) 0.15 on steel nuts and bolts.

CRC® Nickel Anti-Seize is designed for use in:

- Oil refineries and chemical plants.
- Gas and chemical transmission lines.
- Municipal water and power systems.
- Mining.
- Environments where a "clean" inert lubricant is needed.

DIRECTIONS: *Read entire label before using this product.*

1. Clean scale and old compound from thread surfaces. **NOTE: When grinding or wire brushing, use a dust mask.** **2.** Coat mating surfaces and assemble. **3.** Do not use thinner. **4.** To avoid contamination, keep container closed when not in use. **5.** Not for use on oxygen systems.

Danger: May cause an allergic skin reaction. Suspected of causing cancer. Causes damage to organs (respiratory tract) through prolonged or repeated exposure by inhalation.

Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations. **First Aid:** If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Get medical advice/attention if you feel unwell. Wash contaminated clothing before reuse. If exposed or concerned: Get medical attention.

Contains Hydrotreated heavy naphthenic distillates (64742-52-5), Graphite (7782-42-5), Nickel (7440-02-0) and Hydrotreated residual oils (64742-57-0). This product contains a chemical known to the State of California to cause cancer. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

©2015 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS)

Made in U.S.A. 15A
www.crcindustries.com

