

**CRC**

Thread Lubricant

- Perfect for use on Aluminum Conduit and Fittings
- Prevents Seizing and Galling
- Compare to Crouse-Hinds® STL2

**Sta-Lube**

Part No. SL35924 • NET WT. 2 oz (57 g)

**CRC**

THREAD LUBRICANT

CRC® Thread Lubricant is a general purpose lubricant that prevents the seizing and galling of threaded surfaces caused by corrosion.

- Aids in assembly and disassembly
- Prevents rust and corrosion
- Especially effective between parts made of dissimilar metals
- Reduces costly downtime and breakage

CRC® Thread Lubricant is recommended for use on aluminum conduit, bolts, bushings, fittings, flanges, nuts, pipes, plugs, and screws.

DIRECTIONS: *Please read entire label before using this product.*

1. Clean scale and old compound from thread surfaces.
2. Coat mating surfaces and assemble.
3. To avoid contamination, keep container closed when not in use.

Crouse-Hinds® is a registered trademark of Cooper Industries Inc

©2010 CRC Industries, Inc. 800-521-3168 Technical Info
Warminster, PA 18974 800-272-8963 Customer Service
www.crcindustries.com Made in U.S.A. 10A 215-442-6260 MSDS

WARNING: Contains Refined heavy naphthenic distillates 64741-96-4 / 64742-52 and Lithium 12-hydroxystearate 7620-77-1. Frequent or prolonged contact may cause irritation. Avoid contact with skin and eyes. Do not take internally. **FIRST AID:** In case of contact, flush affected area thoroughly with soap and water. If swallowed, do not induce vomiting. Seek medical attention for all overexposures.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations.

KEEP AWAY FROM CHILDREN

