



THREAD LUBRICANT

Thread Lubricant

- Perfect For Use On Aluminum Conduit and Fittings
- Prevents Seizing and Galling
- Compare to Crouse-Hinds® STL8



Part No. SL35925 • NET WT. 8 OZ. (227 g)

CRC® Thread Lubricant is a general purpose lubricant that prevents the seizing and galling of threaded surfaces caused by corrosion.

- Aids in assembly and disassembly
- Prevents rust and corrosion
- Especially effective between parts made of dissimilar metals
- Reduces costly downtime and breakage

CRC® Thread Lubricant is recommended for use on aluminum conduit, bolts, bushings, fittings, flanges, nuts, pipes, plugs, and screws.

DIRECTIONS: *Please read entire label before using this product.*

1. Clean scale and old compound from thread surfaces. 2. Coat mating surfaces and assemble. 3. To avoid contamination, keep container closed when not in use.

WARNING: Contains Refined heavy naphthenic distillates 64741-96-4 / 64742-52 and Lithium 12-hydroxystearate 7620-77-1. Frequent or prolonged contact may cause irritation. Avoid contact with skin and eyes. Do not take internally.

FIRST AID: In case of contact, flush affected area thoroughly with soap and water. If swallowed, DO NOT induce vomiting. Seek medical attention for all overexposures.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations.

KEEP AWAY FROM CHILDREN

Crouse-Hinds® is a registered trademark of Cooper Industries Inc

©2009 CRC Industries, Inc.
Warminster, PA 18974
www.crcindustries.com

800-521-3168 Technical Info
800-272-8963 Customer Service
215-442-6260 MSDS

Made in U.S.A.
09A

