



BALL AND ROLLER BEARING HI-TEMP GREASE

NET 35 LBS (16 Kg.)

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	1	REACTIVITY	1
FLAMMABILITY	0	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

IMPORTANT: DO NOT MIX GREASES OF DIFFERENT BASE TYPE. USE A SOLVENT TO REMOVE AND CLEAN OUT ALL TRACES OF INCOMPATIBLE GREASE BEFORE REPACKING. REPACK ACCORDING TO MANUFACTURERS INSTRUCTIONS.

IMPORTANTE: NO MEZCLE GRASAS DE BASE DIFERENTE.

CAUTION

Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.



First Aid: Eye Contact: Flush with clear water for at least 15 minutes.
If irritation persists, seek medical attention.
Skin Contact: Remove contaminated clothing. Wipe excess material from skin. Wash exposed area with water.
Skin Injections: High pressure skin injections are serious emergencies.
Get immediate medical attention.
Inhalation: Remove from area of exposure.

WARNING

Child can fall into bucket and drown. Keep children away from bucket containing any amount of any liquid.



BALL AND ROLLER

BEARING HI-TEMP GREASE

ALUMINUM COMPLEX, NLGI #2 GRADE GREASE ENGINEERED FOR HIGH TEMPERATURES AND HEAVILY LOADED BUSHINGS AND BALL AND ROLLER BEARINGS. PROVIDES A TOUGH LUBRICANT FILM UNDER A WIDE RANGE OF OPERATING CONDITIONS AND LOADS. TIMKEN OK LOAD 60 LBS; TYPICAL DROP POINT 480F. CONTAINS: HEAVY NAPHTHENIC DISTILLATE; 64742-52-5, RESIDUAL OILS, SOLVENT REFINED 64742-01-4, MOLYBDENUM SULFIDE 1317-33-5, NAPHTHALENESULFONIC ACID, DINONYL 57855-77-3.

KEEP OUT OF REACH OF CHILDREN

For additional information, consult MSDS for this product.

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Sta-Lube
CRC Industries
Warminster, PA 18974
Technical Information 800-521-3168
Customer Service 800-272-8963
MSDS 215-442-6260
For emergencies, call Chemtrec
1-800-424-9300

www.crcindustries.com

Revision #06B



SL3635

PRODUCT CODE

SL3635

BATCH NUMBER

1111/333333

BALL AND ROLLER BEARING HI-TEMP GREASE

NET 35 LBS (16 Kg.)



STA-LUBE®
©1998 CRC Industries, Inc.
Warminster, PA 18974
TECHNICAL INFORMATION: 800-521-3168
CUSTOMER SERVICE: 800-272-8963
Made in USA