




SAFETY DATA SHEET

1. Identification

Product identifier	Rust Proof Enamel OSHA White Spray Paint
Other means of identification	
Product code	18106
Recommended use	Coating
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Company name	CRC Industries, Inc.
Address	885 Louis Dr. Warminster, PA 18974 US
Telephone	
General Information	215-674-4300
Technical Assistance	800-521-3168
Customer Service	800-272-4620
24-Hour Emergency (CHEMTREC)	800-424-9300 (US) 703-527-3887 (International)
Website	www.crcindustries.com

2. Hazard(s) identification

Physical hazards	Flammable aerosols Gases under pressure	Category 1 Liquefied gas
Health hazards	Serious eye damage/eye irritation Carcinogenicity Specific target organ toxicity, single exposure Specific target organ toxicity, repeated exposure	Category 2A Category 2 Category 3 narcotic effects Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		

Signal word

Danger

Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
acetone		67-64-1	30 - 40
isobutyl acetate		110-19-0	10 - 20
propane		74-98-6	10 - 20
n-butane		106-97-8	5 - 10
titanium dioxide		13463-67-7	5 - 10
ethylene glycol propyl ether		2807-30-9	1 - 3
methyl isobutyl ketone		108-10-1	1 - 3
methyl propyl ketone		107-87-9	1 - 3
ethylbenzene		100-41-4	< 0.3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3 100 ppm	
isobutyl acetate (CAS 110-19-0)	PEL	700 mg/m3 150 ppm	
methyl isobutyl ketone (CAS 108-10-1)	PEL	410 mg/m3 100 ppm	
methyl propyl ketone (CAS 107-87-9)	PEL	700 mg/m3 200 ppm	
propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm	
titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value
acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
ethylbenzene (CAS 100-41-4)	TWA	20 ppm
	STEL	150 ppm
isobutyl acetate (CAS 110-19-0)	TWA	50 ppm
	STEL	75 ppm
methyl isobutyl ketone (CAS 108-10-1)	TWA	20 ppm
	STEL	150 ppm
methyl propyl ketone (CAS 107-87-9)	STEL	150 ppm
n-butane (CAS 106-97-8)	STEL	1000 ppm
titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
		TWA
isobutyl acetate (CAS 110-19-0)	TWA	435 mg/m3
		100 ppm
		700 mg/m3
methyl isobutyl ketone (CAS 108-10-1)	STEL	150 ppm
		300 mg/m3
		TWA
methyl propyl ketone (CAS 107-87-9)	TWA	75 ppm
		205 mg/m3
		50 ppm
n-butane (CAS 106-97-8)	TWA	530 mg/m3
		150 ppm
propane (CAS 74-98-6)	TWA	1900 mg/m3
		800 ppm
		1800 mg/m3
		1000 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
methyl isobutyl ketone (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Butyl rubber.
Other	Wear suitable protective clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	White.
Odor	Aromatic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	132.9 °F (56.1 °C) estimated
Flash point	-2.2 °F (-19 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.7 %
Flammability limit - upper (%)	10.9 %
Vapor pressure	2432.1 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.77 - 0.85
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	793.4 °F (423 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	79.6 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Health injuries are not known or expected under normal use.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20000 mg/kg
Inhalation		
LC50	Rat	16000 ppm, 4 hours
Oral		
LD50	Rat	5800 mg/kg
ethylbenzene (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	17800 mg/kg
Inhalation		
LC50	Rat	17.2 mg/l, 4 hours
Oral		
LD50	Rat	3500 mg/kg
ethylene glycol propyl ether (CAS 2807-30-9)		
Acute		
Dermal		
LD50	Rabbit	0.87 g/kg
Oral		
LD50	Rat	4.45 g/kg
methyl isobutyl ketone (CAS 108-10-1)		
Acute		
Dermal		
LD50	Rabbit	> 3 g/kg
Inhalation		
LC50	Rat	8.2 mg/l, 4 Hours
Oral		
LD50	Rat	2080 mg/kg
methyl propyl ketone (CAS 107-87-9)		
Acute		
Oral		
LD50	Rat	3.73 g/kg

Components	Species	Test Results
propane (CAS 74-98-6)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
titanium dioxide (CAS 13463-67-7)		
Acute		
Dermal		
LD50	Rabbit	> 10000 mg/kg
Oral		
LD50	Rat	> 10000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
methyl isobutyl ketone (CAS 108-10-1)	2B Possibly carcinogenic to humans.
titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

Components	Species	Test Results
acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours
ethylbenzene (CAS 100-41-4)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 2.1 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 12.1 mg/l, 96 hours
methyl isobutyl ketone (CAS 108-10-1)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 492 - 593 mg/l, 96 hours

Components	Species	Test Results
methyl propyl ketone (CAS 107-87-9)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 1190 - 1290 mg/l, 96 hours
titanium dioxide (CAS 13463-67-7)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) > 1000 mg/l, 48 hours
<i>Acute</i>		
Fish	LC50	Fathead minnow (Pimephales promelas) 1000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

acetone	-0.24
ethylbenzene	3.15
isobutyl acetate	1.78
methyl isobutyl ketone	1.31
methyl propyl ketone	0.91
n-butane	2.89
propane	2.36

Bioconcentration factor (BCF)

titanium dioxide	352
------------------	-----

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity

Transport hazard class(es)**Class** 2.1**Subsidiary risk** -**Packing group** Not applicable.**ERG Code** 10L**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Other information****Passenger and cargo aircraft** Allowed with restrictions.**Cargo aircraft only** Allowed with restrictions.**IMDG****UN number** UN1950**UN proper shipping name** AEROSOLS, Limited Quantity**Transport hazard class(es)****Class** 2**Subsidiary risk** -**Packing group** Not applicable.**Environmental hazards****Marine pollutant** No.**EmS** F-D, S-U**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**15. Regulatory information****US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

ethylbenzene (CAS 100-41-4)

ethylene glycol propyl ether (CAS 2807-30-9)

methyl isobutyl ketone (CAS 108-10-1)

CERCLA Hazardous Substances: Reportable quantity

acetone (CAS 67-64-1) 5000 LBS

isobutyl acetate (CAS 110-19-0) 5000 LBS

methyl isobutyl ketone (CAS 108-10-1) 5000 LBS

CERCLA Hazardous Substance List (40 CFR 302.4)

acetone (CAS 67-64-1) Listed.

ethylene glycol propyl ether (CAS 2807-30-9) Listed.

isobutyl acetate (CAS 110-19-0) Listed.

methyl isobutyl ketone (CAS 108-10-1) Listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ethylene glycol propyl ether (CAS 2807-30-9)

methyl isobutyl ketone (CAS 108-10-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

acetone (CAS 67-64-1) 6532

methyl isobutyl ketone (CAS 108-10-1) 6715

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

acetone (CAS 67-64-1) 35 %WV
methyl isobutyl ketone (CAS 108-10-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

acetone (CAS 67-64-1) 6532
methyl isobutyl ketone (CAS 108-10-1) 6715

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

acetone (CAS 67-64-1) Low priority
isobutyl acetate (CAS 110-19-0) Low priority
methyl isobutyl ketone (CAS 108-10-1) Low priority
methyl propyl ketone (CAS 107-87-9) Low priority

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

acetone (CAS 67-64-1)
ethylbenzene (CAS 100-41-4)
ethylene glycol propyl ether (CAS 2807-30-9)
methyl isobutyl ketone (CAS 108-10-1)
n-butane (CAS 106-97-8)
titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

acetone (CAS 67-64-1)
ethylbenzene (CAS 100-41-4)
ethylene glycol propyl ether (CAS 2807-30-9)
isobutyl acetate (CAS 110-19-0)
methyl isobutyl ketone (CAS 108-10-1)
methyl propyl ketone (CAS 107-87-9)
n-butane (CAS 106-97-8)
propane (CAS 74-98-6)
titanium dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

acetone (CAS 67-64-1)
isobutyl acetate (CAS 110-19-0)
methyl isobutyl ketone (CAS 108-10-1)
methyl propyl ketone (CAS 107-87-9)
n-butane (CAS 106-97-8)
propane (CAS 74-98-6)
titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

acetone (CAS 67-64-1)
ethylbenzene (CAS 100-41-4)
ethylene glycol propyl ether (CAS 2807-30-9)
isobutyl acetate (CAS 110-19-0)
methyl isobutyl ketone (CAS 108-10-1)
methyl propyl ketone (CAS 107-87-9)
n-butane (CAS 106-97-8)
propane (CAS 74-98-6)
titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

acetone (CAS 67-64-1)
ethylbenzene (CAS 100-41-4)
isobutyl acetate (CAS 110-19-0)

methyl isobutyl ketone (CAS 108-10-1)
methyl propyl ketone (CAS 107-87-9)
n-butane (CAS 106-97-8)
propane (CAS 74-98-6)
titanium dioxide (CAS 13463-67-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
methyl isobutyl ketone (CAS 108-10-1)	Listed: November 4, 2011
titanium dioxide (CAS 13463-67-7)	Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

methyl isobutyl ketone (CAS 108-10-1)	Listed: March 28, 2014
---------------------------------------	------------------------

Volatile organic compounds (VOC) regulations

EPA

Aerosol coatings (40 CFR 59, Subpt. E) Compliant

State

Aerosol coatings This product is regulated as a Non-Flat Paint. This product is compliant for sale in all 50 states.

Maximum incremental reactivity (MIR) 0.68

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	11-18-2016
Prepared by	Allison Cho
Version #	01
Further information	Not available.
HMIS® ratings	Health: 2* Flammability: 4 Physical hazard: 1 Personal protection: B
NFPA ratings	Health: 2 Flammability: 4 Instability: 1

NFPA ratings**Disclaimer**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision Information

This document has undergone significant changes and should be reviewed in its entirety.